

E-mail to: info@bappu.de

ELK GmbH • Gladbacher Str. 232 • D-47805 Krefeld • www.bappu.de

Phone +49 2151 – 788 86-01
 Fax +49 2151 – 788 86-02



Order

Factory calibration and adjustment

pls mark	Name	Description	Price*	Devices Serial number
<input type="checkbox"/>	BAPPU-classic	Factory calibration ¹ and adjustment of all measuring range (standard version); incl. Batteries	204,00 €	
		<input type="checkbox"/> with optional output calibration plus	91,00 €	
<input type="checkbox"/>	BAPPU-evo	Factory calibration ¹ and adjustment of all measuring range(standard version)	188,00 €	
		<input type="checkbox"/> with optional output calibration plus	91,00 €	
<input type="checkbox"/>	Anemometer	Factory calibration ¹ and adjustment of anemometer	68,00 €	
		<input type="checkbox"/> with optional output calibration plus	28,00 €	
<input type="checkbox"/>	IAQ-probe VOCOSx	Factory calibration ¹ and adjustment; price depending on the version ² :		
		<input type="checkbox"/> with CO ₂ -sensor	73,00 €	
		<input type="checkbox"/> with VOC-sensor	48,00 €	
		<input type="checkbox"/> with CO-sensor plus	61,00 €	
		<input type="checkbox"/> with particulate matter sensor plus	131,00 €	
		<input type="checkbox"/> with optional output calibration plus	30,00 €	
<input type="checkbox"/>	Globe-Thermometer	Factory calibration ¹	53,00 €	
<input type="checkbox"/>	H-A-Calibrator	Calibration acoustic calibrator class 2	90,00 €	
Total order value:				
The prices are plus 19% VAT and shipping costs (18,- € per device within Germany).				

*Price changes and technical changes reserved. Prices are per device.

By default, a calibration is carried out at the input of the device. Subsequently, all measuring ranges are readjusted. An output calibration (after adjustment) is available as an option. All devices undergo a functional and plausibility check before delivery and comply with the technical specifications and measuring tolerances of the respective device.

- 1) The factory calibration always includes the adjustment of the measuring ranges if required. If an output calibration certificate (additional calibration after adjustment) is required, this must be known at the latest with the input of the device. There are additional costs for this. Retroactively, no output calibration certificate can be created.
- 2) Only the calibration and adjustment of all installed sensors of the IAQ sensor is possible.

send the order to:

		e-mail (also for billing)
contact person	phone	customer number
company		
street		
postal code, city, country		

The invoice is sent electronically to the above mail address. If the billing address differs from the above delivery address, we ask for a separate message.

place and date

signature / stamp
(customer)

valid from: january 2023